



## Brake Adjustment Limits - Clamp-type Chambers

Size	Marking	Outside Diameter	Adjustment Limit
6	None	4-1/2" (115mm)	1-1/4" (32mm)
9	None	5-1/4" (133mm)	1-3/8" (35mm)
12	None	5-11/16" (144mm)	1-3/8" (35mm)
16	None	6-3/8" (162mm)	1-3/4" (45mm)
16 L	L Stamped In Cover, Stroke Tag	6-3/8" (162mm)	2" (51mm)
20	None	6-25/32" (172mm)	1-3/4" (45mm)
20 L	L Stamped In Cover, Stroke Tag	6-25/32" (172mm)	2" (51mm)
24	None	7-7/32" (183mm)	1-3/4" (45mm)
24 L	L Stamped In Cover, Stroke Tag	7-7/32" (183mm)	2" (51mm)
24 LS	Square Ports, Tag & Cover Marking	7-7/32" (183mm)	2-1/2" (64mm)
30	None	8-3/32" (205mm)	2" (51mm)
30	DD3 (Bus/Coach)	8-1/8" (206mm)	2-1/4" (57mm)
30 LS	Square Ports, Tag & Cover Marking	8-3/32" (205mm)	2-1/2" (57mm)
36	None	9" (228mm)	2-1/4" (57mm)
<p>"L" denotes the long-stroke pushrod design.  "LS" denotes the long-stroke pushrod design with square ports.</p>			